

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 3 of 26

Amendments to the Claims

This listing of claims will replace all prior versions, and listing, of claims in the application.

Listing of Claims:

1. (Canceled)

2. (Currently Amended) ~~The display device of claim 1. A display device comprising:~~

~~_____ an active matrix substrate;~~

~~_____ a counter electrode;~~

~~_____ a display medium layer interposed between the active matrix substrate and the counter electrode; and~~

~~_____ a plurality of pixels,~~

~~_____ wherein the active matrix substrate includes:~~

~~_____ a base plate;~~

~~_____ a plurality of pixel electrodes formed on the base plate, each said pixel electrode being associated with one of the plurality of pixels;~~

~~_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;~~

~~_____ a plurality of gate lines for controlling operations of the pixel switching elements;~~

~~_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;~~

~~_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;~~

~~_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;~~

REST AVAILABLE COPY

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 4 of 26

_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements; and

_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements,

_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and

wherein each said pixel switching element and each said data line switching element are thin-film transistors that have substantially the same channel length, and

wherein a ratio of a channel width of each said pixel switching element to an electrostatic capacitance of associated one of the pixels is substantially equal to a ratio of a channel width of each said data line switching element to an electrostatic capacitance of associated one of the data lines.

3. (Currently Amended) The display device of claim 1, wherein each said pixel switching element and each said data line switching element are thin-film transistors, and wherein the thin-film transistors have channels extending in parallel with each other.

4. (Currently Amended) ~~The display device of claim 1;~~ A display device comprising:
_____ an active matrix substrate;

_____ a counter electrode;

_____ a display medium layer interposed between the active matrix substrate and the counter electrode; and

_____ a plurality of pixels,

_____ wherein the active matrix substrate includes:

_____ a base plate;

_____ a plurality of pixel electrodes formed on the base plate, each said pixel electrode being associated with one of the plurality of pixels;

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 5 of 26

_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;

_____ a plurality of gate lines for controlling operations of the pixel switching elements;

_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;

_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;

_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;

_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements; and

_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements,

_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and

wherein each said pixel switching element is an n-channel transistor or a p-channel transistor, and

wherein if the pixel switching element is an n-channel transistor, each said data line switching element is a p-channel transistor, and

wherein if the pixel switching element is a p-channel transistor, the data line switching element is an n-channel transistor.

5. (Original) The display device of claim 4, wherein the pixel switching element is an n-channel transistor and the data line switching element is a p-channel transistor.

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 6 of 26

6. (Currently Amended) The display device of claim 1: ~~A display device comprising:~~
~~_____ an active matrix substrate;~~
~~_____ a counter electrode;~~
~~_____ a display medium layer interposed between the active matrix substrate and the counter electrode; and~~
~~_____ a plurality of pixels,~~
~~_____ wherein the active matrix substrate includes:~~
~~_____ a base plate;~~
~~_____ a plurality of pixel electrodes formed on the base plate, each said pixel electrode being associated with one of the plurality of pixels;~~
~~_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;~~
~~_____ a plurality of gate lines for controlling operations of the pixel switching elements;~~
~~_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;~~
~~_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;~~
~~_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;~~
~~_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements; and~~
~~_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements,~~
~~_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and~~

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 7 of 26

wherein each said pixel switching element is an n-channel transistor or a p-channel transistor, while each said data line switching element includes an n-channel transistor and a p-channel transistor that are connected in parallel with each other, and

wherein in the data line switching element, one of the p-and n-channel transistors that has a polarity different from that of the pixel switching element has a *channel* length or channel width greater than that of the other transistor.

7. (Currently Amended) The display device of ~~claim 1~~ claim 2, wherein each said pixel switching element and each said data line switching element both have a semiconductor layer, which has been deposited on the base plate, as a transistor active region.

8. (Currently Amended) The display device of ~~claim 1~~ claim 2, wherein the display medium layer is a liquid crystal layer.

Claims 9 – 13 (Canceled)

14. (Currently Amended) ~~The display device of claim 13;~~ A display device comprising:
~~_____ a pair of substrates that is disposed so as to face each other and be spaced apart from each other;~~
~~_____ a display medium layer interposed between the pair of substrates; and~~
~~_____ a plurality of pixels,~~
~~_____ wherein a plurality of counter signal electrodes, each of which extends in a column direction and through which a data signal is supplied, are formed on one of the pair of substrates, and~~
~~_____ wherein the other of the pair of substrate includes:~~
~~_____ a plurality of pixel electrodes arranged in matrix, each said pixel electrode being associated with one of the plurality of pixels;~~

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 8 of 26

~~_____ a plurality of pixel switching elements, each of which is connected to associated one of the pixel electrodes;~~

~~_____ a plurality of gate lines, which extend in a row direction and are used for controlling operations of the pixel switching elements; and~~

~~_____ a plurality of common lines, each of which is connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements, and~~

~~_____ wherein the display device further includes:~~

~~_____ a plurality of signal electrode switching elements, each of which is connected to associated one of the counter signal electrodes and controls supply of the data signal to the counter signal electrode, and~~

~~_____ a plurality of signal electrode transfer sections, each of which is used to ensure electrical connection between each of the signal electrode switching elements and associated one of the counter signal electrodes,~~

~~_____ wherein a signal to turn ON the signal electrode switching elements and a signal to turn ON the pixel switching elements have the same polarity, and~~

~~_____ wherein the signal electrode switching elements and the pixel switching elements are formed on the same substrate, and~~

~~_____ wherein the display device further comprises a plurality of signal electrode transfer sections, each of which is used to ensure electrical connection between each of the signal electrode switching elements and associated one of the counter signal electrodes;~~

15. (Currently Amended) ~~The display device claim 13,~~ A display device comprising:

~~_____ a pair of substrates that is disposed so as to face each other and be spaced apart from each other;~~

~~_____ a display medium layer interposed between the pair of substrates; and~~

~~_____ a plurality of pixels,~~

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 9 of 26

_____ wherein a plurality of counter signal electrodes, each of which extends in a column direction and through which a data signal is supplied, are formed on one of the pair of substrates, and

_____ wherein the other of the pair of substrate includes:

_____ a plurality of pixel electrodes arranged in matrix, each said pixel electrode being associated with one of the plurality of pixels;

_____ a plurality of pixel switching elements, each of which is connected to associated one of the pixel electrodes;

_____ a plurality of gate lines, which extend in a row direction and are used for controlling operations of the pixel switching elements; and

_____ a plurality of common lines, each of which is connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements,

_____ wherein the display device further includes a plurality of signal electrode switching elements, each of which is connected to associated one of the counter signal electrodes and controls supply of the data signal to the counter signal electrode, and

_____ wherein a signal to turn ON the signal electrode switching elements and a signal to turn ON the pixel switching elements have the same polarity, and

wherein each said pixel switching element and each said signal electrode switching element are thin-film transistors that have substantially the same channel length, and

wherein a ratio of a channel width of each said pixel switching element to an electrostatic capacitance of associated one of the pixels is substantially equal to a ratio of a channel width of each said signal electrode switching element to an electrostatic capacitance of associated one of the counter signal electrodes.

16. (Currently Amended) The display device of ~~claim 13~~ claim 14, wherein each said pixel switching element and each said signal electrode switching element are thin-film transistors, and

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 10 of 26

wherein channels of the thin-film transistors extend substantially in parallel with each other.

17. (Currently Amended) The display device of ~~claim 13~~ claim 14, wherein each said pixel switching element and each said signal electrode switching element are both n-channel transistors.

18. (Currently Amended) The display device of ~~claim 13~~ claim 14, wherein each said pixel switching element and each said signal electrode switching element are both p-channel transistors.

19. (Currently Amended) The display device of ~~claim 13~~ claim 14, wherein the display medium layer is a liquid crystal layer.

20. (Canceled)

21. (Canceled)

22. (Currently Amended) The display device of ~~claim 1~~ claim 2, wherein a potential drop (or rise) associated with the data line switching elements being turned from ON to OFF is almost equal to a potential drop (or rise) associated with the pixel switching elements being turned from ON to OFF.

23. (Currently Amended) The display device of ~~claim 1~~, A display device comprising:
_____ an active matrix substrate;
_____ a counter electrode;
_____ a display medium layer interposed between the active matrix substrate and the counter electrode; and

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 11 of 26

~~_____ a plurality of pixels,~~
~~_____ wherein the active matrix substrate includes:~~
~~_____ a base plate;~~
~~_____ a plurality of pixel electrodes formed on the base plate, each said pixel electrode being associated with one of the plurality of pixels;~~
~~_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;~~
~~_____ a plurality of gate lines for controlling operations of the pixel switching elements;~~
~~_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;~~
~~_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;~~
~~_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;~~
~~_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements; and~~
~~_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements,~~
~~_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and~~
wherein a potential drop (or rise) associated with the data line switching elements being turned from ON to OFF and a potential drop (or rise) associated with the pixel switching elements being turned from ON to OFF is such as to minimize a variation in voltage being applied to the display medium.

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 12 of 26

24. (Currently Amended) The display device of ~~claim 1~~, claim 2, wherein voltages supplied to the data lines and the signal lines have mutually different polarity.

25. (Currently Amended) ~~The display device of claim 1, further comprising: A display device comprising:~~

- ~~_____ an active matrix substrate;~~
- ~~_____ a counter electrode;~~
- ~~_____ a display medium layer interposed between the active matrix substrate and the counter electrode; and~~
- ~~_____ a plurality of pixels,~~
- ~~_____ wherein the active matrix substrate includes:~~
 - ~~_____ a base plate;~~
 - ~~_____ a plurality of pixel electrodes formed on the base plate, each said pixel electrode being associated with one of the plurality of pixels;~~
 - ~~_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;~~
 - ~~_____ a plurality of gate lines for controlling operations of the pixel switching elements;~~
 - ~~_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;~~
 - ~~_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;~~
 - ~~_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;~~
 - ~~_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements;~~

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 13 of 26

_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements;

_____ a power supply having a voltage range for supplying voltages to the data lines; and

_____ a power supply having a voltage range for supplying voltages to the counter electrode;

and

_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and

_____ wherein one of (1) the voltage range of the power supply for supplying voltages to the data lines is within the voltage range of the power supply for supplying voltages to the counter electrode or (2) the voltage range of the power supply for supplying voltages to the counter electrode is within the voltage range of the power supply for supplying voltages to the data lines.

26. (Currently Amended) The display device of claim 1; A display device comprising:

_____ an active matrix substrate;

_____ a counter electrode;

_____ a display medium layer interposed between the active matrix substrate and the counter electrode; and

_____ a plurality of pixels,

_____ wherein the active matrix substrate includes:

_____ a base plate;

_____ a plurality of pixel electrodes formed on the base plate, each said pixel electrode being associated with one of the plurality of pixels;

_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;

_____ a plurality of gate lines for controlling operations of the pixel switching elements;

_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 14 of 26

_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;

_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;

_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements; and

_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements,

_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and

wherein a potential drop (or rise) associated with the data line switching elements being turned from ON to OFF and a potential drop (or rise) associated with the pixel switching elements being turned from ON to OFF is such that unfavorable direct current components are further reduced and so that a voltage at a level closer to a desired voltage is applied to the display medium.

27. (Canceled)

28. (Canceled)

29. (Currently Amended) The active matrix substrate of claim 10, further comprising:
An active matrix substrate comprising:

_____ a base plate;

_____ a plurality of pixel electrodes formed on the base plate;

_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;

_____ a plurality of gate lines for controlling operations of the pixel switching elements;

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 15 of 26

_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;

_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;

_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;

_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements;

_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements;

a power supply having a voltage range for supplying voltages to the data lines; and

a power supply having a voltage range for supplying voltages to the counter electrode;

and

_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and

wherein one of (1) the voltage range of the power supply for supplying voltages to the data lines is within the voltage range of the power supply for supplying voltages to the counter electrode or (2) the voltage range of the power supply for supplying voltages to the counter electrode is within the voltage range of the power supply for supplying voltages to the data lines.

30. (Canceled)

31. (Currently Amended) The display device of claim 11, A display device comprising a display region unit, wherein the display region unit includes:

_____ a substrate on which a plurality of pixels are arranged in columns and rows;

_____ a driver for driving the pixels;

Applicant: Hisashi Nagata, et al.

U.S.S.N.: 10/024,065

RESPONSE TO FINAL OFFICE ACTION

Page 16 of 26

switching means, formed on the substrate, for changing an electrical connection state between the pixels and the driver; and

wherein the switching means includes:

a first switching element located closer to one of the pixels,

a second switching element located closer to the driver,

wherein a signal to turn ON the first switching element and a signal to turn ON the second switching element have mutually different polarities, and

wherein a potential drop (or rise) associated with the first switching element being turned from ON to OFF and a potential drop (or rise) associated with the second switching element being turned from ON to OFF is such as to minimize a variation in voltage being applied to a display medium.

32. (Currently Amended) ~~The display device of claim 11, A display device comprising a display region unit, wherein the display region unit includes:~~

~~a substrate on which a plurality of pixels are arranged in columns and rows;~~

~~a driver for driving the pixels; and~~

~~switching means, formed on the substrate, for changing an electrical connection state between the pixels and the driver; and~~

~~wherein the switching means includes:~~

~~a first switching element located closer to one of the pixels,~~

~~a second switching element located closer to the driver,~~

~~wherein a signal to turn ON the first switching element and a signal to turn ON the second switching element have mutually different polarities, and~~

wherein a potential drop (or rise) associated with the first switching element being turned from ON to OFF and a potential drop (or rise) associated with the second switching element being turned from ON to OFF is such that unfavorable direct current components are further reduced and so that a voltage at a level closer to a desired voltage is applied to a display medium.

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 17 of 26

33. (Currently Amended) The display device of ~~claim 11~~ claim 31, wherein voltages supplied to the data lines and the signal lines have mutually different polarity.

34. (Currently Amended) ~~The display device of claim 11, further comprising:~~ A display device comprising a display region unit, wherein the display region unit includes:
_____ a substrate on which a plurality of pixels are arranged in columns and rows;
_____ a driver for driving the pixels; and
_____ switching means, formed on the substrate, for changing an electrical connection state between the pixels and the driver,
_____ wherein the switching means includes:
_____ a first switching element located closer to one of the pixels,
_____ a second switching element located closer to the driver, and
_____ wherein a signal to turn ON the first switching element and a signal to turn ON the second switching element have mutually different polarities;
a power supply having a voltage range for supplying voltages to the data lines;
a power supply having a voltage range for supplying voltages to the counter electrode;
and

wherein one of (1) the voltage range of the power supply for supplying voltages to the data lines is within the voltage range of the power supply for supplying voltages to the counter electrode or (2) the voltage range of the power supply for supplying voltages to the counter electrode is within the voltage range of the power supply for supplying voltages to the data lines.

35. (Canceled)

36. (Currently Amended) ~~The display driving method of claim 12;~~ A method for driving a display device, the display device comprising:
_____ an active matrix substrate;

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 18 of 26

_____ a counter substrate, which is disposed so as to face the active matrix substrate and includes a counter electrode; and
_____ a display medium layer interposed between the active matrix and counter substrates,
_____ wherein the active matrix substrate includes:
_____ a base plate;
_____ a plurality of pixel electrodes formed on the base plate;
_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;
_____ a plurality of gate lines for controlling operations of the pixel switching elements;
_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;
_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;
_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;
_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements; and
_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements,
_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and
_____ wherein the method drives the display device in such a manner that an interval, in which one of the pixel switching elements is turned OFF to hold a potential level of associated one of the data lines as applied to associated one of the pixel electrodes, overlaps at least partially with an interval, in which one of the data line switching elements that is associated with the data line

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 19 of 26

is turned OFF to hold a potential level of the data signal on the data line, for the pixel electrode and the counter electrode that face each other via the display medium layer, and

wherein a potential drop (or rise) associated with the data line switching elements being turned from ON to OFF and a potential drop (or rise) associated with the pixel switching elements being turned from ON to OFF is such as to minimize a variation in voltage being applied to the display medium.

37. (Currently Amended) The display driving method of claim 12; A method for driving a display device, the display device comprising:

_____ an active matrix substrate;

_____ a counter substrate, which is disposed so as to face the active matrix substrate and includes a counter electrode; and

_____ a display medium layer interposed between the active matrix and counter substrates,

_____ wherein the active matrix substrate includes:

_____ a base plate;

_____ a plurality of pixel electrodes formed on the base plate;

_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;

_____ a plurality of gate lines for controlling operations of the pixel switching elements;

_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;

_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;

_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 20 of 26

_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements; and

_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements,

_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities, and

_____ wherein the method drives the display device in such a manner that an interval, in which one of the pixel switching elements is turned OFF to hold a potential level of associated one of the data lines as applied to associated one of the pixel electrodes, overlaps at least partially with an interval, in which one of the data line switching elements that is associated with the data line is turned OFF to hold a potential level of the data signal on the data line, for the pixel electrode and the counter electrode that face each other via the display medium layer, and

wherein a potential drop (or rise) associated with the data line switching elements being turned from ON to OFF and a potential drop (or rise) associated with the pixel switching elements being turned from ON to OFF is such that unfavorable direct current components are further reduced and so that a voltage at a level closer to a desired voltage is applied to the display medium.

38. (Currently Amended) The display driving method of ~~claim 12~~ claim 36, wherein voltages supplied to the data lines and the signal lines have mutually different polarity.

39. (Currently Amended) ~~The display driving method of claim 12, wherein the display device further comprises: A method for driving a display device, the display device comprising:~~

_____ an active matrix substrate;

_____ a counter substrate, which is disposed so as to face the active matrix substrate and includes a counter electrode; and

_____ a display medium layer interposed between the active matrix and counter substrates.

Applicant: Hisashi Nagata, et al.
U.S.S.N.: 10/024,065
RESPONSE TO FINAL OFFICE ACTION
Page 21 of 26

_____ wherein the active matrix substrate includes:

_____ a base plate;

_____ a plurality of pixel electrodes formed on the base plate;

_____ a plurality of pixel switching elements, each said pixel switching element being connected to associated one of the pixel electrodes;

_____ a plurality of gate lines for controlling operations of the pixel switching elements;

_____ a plurality of data lines, each said data line being connected to associated ones of the pixel electrodes by way of associated ones of the pixel switching elements so as to supply a data signal therethrough;

_____ a plurality of data line switching elements, each said data line switching element having terminals, one of said terminals being connected to associated one of the data lines;

_____ a plurality of signal input terminals, each said signal input terminal being connected to another terminal of associated one of the data line switching elements and another terminal of another associated one of the data line switching elements;

_____ a data line branching section, which is provided between the signal input terminals and the data line switching elements;

_____ a control line, which is connected to the data line switching elements to selectively turn ON or OFF the data line switching elements;

_____ a power supply having a voltage range for supplying voltages to the data lines;

_____ a power supply having a voltage range for supplying voltages to the counter electrode;

and

_____ wherein one of (1) the voltage range of the power supply for supplying voltages to the data lines is within the voltage range of the power supply for supplying voltages to the counter electrode or (2) the voltage range of the power supply for supplying voltages to the counter electrode is within the voltage range of the power supply for supplying voltages to the data lines,

and

_____ wherein a signal to turn ON the data line switching elements and a signal to turn ON the pixel switching elements have mutually different polarities; and

Applicant: Hisashi Nagata, et al.

U.S.S.N.: 10/024,065

RESPONSE TO FINAL OFFICE ACTION

Page 22 of 26

wherein the method drives the display device in such a manner that an interval, in which one of the pixel switching elements is turned OFF to hold a potential level of associated one of the data lines as applied to associated one of the pixel electrodes, overlaps at least partially with an interval, in which one of the data line switching elements that is associated with the data line is turned OFF to hold a potential level of the data signal on the data line, for the pixel electrode and the counter electrode that face each other via the display medium layer.

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER: _____**

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.